MINI HYBRID SERIES CONNECTOR



Mini Hybrid Connector – A compact, single connection point with a smaller form factor that is ideal for use in low-pressure applications where ease of use and ergonomics are important. This connector makes it easy to connect power, signal and gases in one simple motion.

FEATURES	BENEFITS
Easy-to-use breakaway design	Quick, automatic disconnect
Small package design	Minimize device size
Streamlined exterior	Clean, attractive appearance
Proven design	Accelerate product development

Specifications • • •



PRESSURE:

Vacuum to 25 psi, 1.7 bar

TEMPERATURE:

40°F to 80°F (4°C to 27°C)

MATERIALS:

External coupler components: PET Air coupler components: Acetal

Springs: Stainless steel

Panel Mount Nut: Zinc-plated steel

Electrical contacts: Gold-plated copper alloy

O-rings: Buna-N Air line: PVC

COLOR: Gray

EXTERNAL UMBILICAL HOSE: 4 feet

(121 cm) PVC

WIRE: 22AWG PVC jacket

TERMINATIONS:

Panel: 1/16" hose barb and two 22AWG wires

with 11" pigtail

Umbilical: 4' (121 cm) umbilical with one 1/16" ID PVC tube and two 22AWG wires with 6" pigtail


Number of air lines: 1

ELECTRICAL SPECIFICATIONS

Voltage: Up to 24VDC **Current:** Up to 3 Amps Wire: 22AWG with PVC jacket Number of contacts: 2

MINI HYBRID SERIES DIMENSIONS

Panel Dimensions





Coupling Hose • PET AND ACETAL



Coupling Panel • PET AND ACETAL





美国CPC_Colder Products Company快速接头和连接器 **NOTES:** 授权西北代理商联系方式

西安嘉岳自动化技术有限公司 Garye Automation Company

地址:西安市未央区未央大道138-1号中登大厦A座十二层

电话: 029 - 8647 4991 邮编: 710016

传真: 029 - 8647 3942 公司QQ:3180038393

手机: 182 9256 1696 E-mail: sales@garye.cn Web: http://www.garye.cn