SANIQUIK[™] SERIES CONNECTOR

Specifications • • •







PRESSURE:

Vacuum to 60 psi, 4.1 bar

TEMPERATURE:

-40°F to 300°F (-40°C to 149°C)

MATERIALS:

Main component: 316L stainless steel **0-rings:** Silicone (clear), platinum-cured, USP Class VI, ADCF

STERILIZATION: Autoclave

TERMINATION SIZES:

3/4" and 1-1/2" sanitary

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC's products in their own application conditions.

CPC's SaniQuik[™] connection answers the question of how to integrate single-use components with your existing stainless processing equipment. This integral sanitary termination attaches to hard-plumbed systems with tri-clover clamps. Once attached it permits quick and easy connection to single-use bag systems, manifolds or tube sets with CPC disposable coupling bodies. SaniQuik connections reduce sanitary gasket replacement, enabling cost-effective media transfer solutions for feeding, harvesting or sampling applications.

Mates with MPC and MPX bodies, inserts and sealing plugs and Backto-Back Adapters (pages 106-111).

FEATURES

3/4" and 1-1/2" sanitary standard terminations

Compatible with MPC and MPX Series couplings

Integral coupling adaptor

ADCF-free materials

BENEFITS


Connect to hard plumbed systems with sanitary gaskets and sanitary clamps

Quick and easy connections to industry standard plastic couplings on single-use bag and tube sets

Disconnecting coupling reduces sanitary gasket replacement

Meet BSE/TSE requirements

SANIQUIK[™] SERIES CONNECTOR DIMENSIONS



A = Height/Diameter B = Total Length

Connections • 316L STAINLESS



DESCRIPTION SILICONE SEAL USP CLASS VI

SQCC221212M SQCC222424M SQCX221212M

PART NO.

2260100

2260200

MPC Series MPC Series MPX Series SQCX222416M MPX Series SQCX222424M MPX Series

MATING SANITARY COUPLING SIZE 3/4" 1-1/2" 3/4" 1-1/2" 1-1/2"

SANITARY BORE 3/4" 1-1/2" 3/4" 1" 1-1/2"

.98" (24.9) 1.98" (50.3) .98" (24.9) 1.98" (50.3) 1.98" (50.3)

1.39" (35.3) 1.50" (38.1) 1.43" (39.1) 1.50" (38.1) 1.50" (38.1)

Accesories • SILICONE (CLEAR)

SEALS

DESCRIPTION PLATINUM-CURED **USP CLASS VI** REPLACEMENT

MATING SANIQUIK

SQCC221212M, SQCC222424M

SQCX221212M, SQCX222416M, SQCX222424M

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters.

NOTES:

美国CPC_Colder Products Company快速接头和连接器 授权西北代理商联系方式

西安嘉岳自动化技术有限公司 Garye Automation Company

地址:西安市未央区未央大道138-1号中登大厦A座十二层

电话: 029 - 8647 4991 邮编: 710016

传真: 029 - 8647 3942 公司QQ:3180038393

手机: 182 9256 1696 E-mail: sales@garye.cn

Web: http://www.garye.cn